

DM on Pneu Flex Arm

The DM Dual Mag stereoscope together with the Pneu (new) Flex Arm is a symbol of functionality and ingenuity, allowing vertical, horizontal, and complete 360° adjustments. This versatile system gives you control of your space and the knowledge that your scope is secure. The DM's large optics produce increased width, working distance and depth of focus. The included 0.5 supplementary lens doubles your field of view, expands your magnification options, and extends your working distance for hands-under work-space. The recommended 48-bulb LED ring light focuses bright, cool, shadow-free daylight illumination directly onto your work. The DM is the best quality dual-magnification scope in the dental, electronic, and industrial markets.



Optional 48 Bulb LED Ring Light Available

CONSTRUCTION

Aluminum alloy construction
Acid and reagent resistant finish

HEAD

Binocular, dual mag 10/20, 10/30, 20/40
Inclined 45°, rotates 360°
10X/20 WF eyepieces
30mm eye tube diameter
Interpupillary distance adjustment 55-75mm
Optional 5X, 15X, and 20X eyepieces

OBJECTIVES (3 CHOICES)

1X/2X, 1X/3X, or 2X/4X paired objectives
0.5X supplementary lens included
Protective lens available

ADJUSTMENT CONTROLS

Rack & pinion focusing
Tension adjustment on pneumatic horizontal arm
Adjustable-width c-clamp for mounting to a bench
Optional screw-down table flange for direct bench mount

ILLUMINATION

Ambient bench light may be sufficient
Optional ring lights offer shadow-free illumination and are highly recommended

DM on Pneu Flex Arm

Model #	Description
DMM-S12N-PA77	DM 10X / 20X on Pneu Flex Arm
DMM-S13N-PA77	DM 10X / 30X on Pneu Flex Arm
DMM-S24N-PA77	DM 20X / 40X on Pneu Flex Arm
ILL-LEDV-R483	LED Ring Light – 48 bulb

WEIGHT AND DIMS

DM Head: 2.6lbs (2.54kg)
Pneumatic Arm: 13.89lbs (6.3kg)
Maximum Radius: 14.96" (380mm)
Minimum Radius: 10.83" (275mm)



P 770.270.1394
F 770.270.2389

865 Marathon Parkway
Lawrenceville GA 30046

LWScientific.com